

## WABO® NEOLUBE

Version 2.2

07/26/2006

### 1. PRODUCT AND COMPANY INFORMATION

Company : **Watson Bowman Acme Corporation**  
95 Pineview Drive  
Amherst, NY 14228

Telephone : 716-691-7566

Emergency telephone number : (800) 424-9300  
(703) 527-3887 (Outside Continental US)

Product name : WABO® NEOLUBE

MSDS ID No. : 10492

TSCA Inventory : All components of this product are included, or are exempt from inclusion, in the EPA Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

Canadian DSL : All components of this product are included, or are exempt from inclusion, in the Canadian Domestic Substance List (DSL).

### 2. HAZARDOUS INGREDIENTS

<u>Chemical</u>	<u>CAS No.</u>	<u>TLV</u>	<u>STEL</u>	<u>PEL</u>	<u>CEIL</u>	<u>Weight %</u>
TOLUENE	108-88-3	50 ppm	150 ppm	N.E.	300 ppm	40.00 - 70.00 %
XYLENE	1330-20-7	100 ppm	150 ppm	100 ppm	300 ppm	5.00 - 10.00 %
ETHYL BENZENE	100-41-4	100 ppm	125 ppm	100 ppm	N.E.	1.00 - 5.00 %

### 3. HAZARDS IDENTIFICATION

HMIS® Rating : HEALTH 3 FLAMMABILITY 3 PHYSICAL HAZARD 0

WHMIS Class : D2B  
B2

Primary Routes of Entry : Ingestion  
Inhalation  
Eye contact  
Skin contact

#### Effects of Overexposure

Inhalation : Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. Inhalation of high vapor concentrations can cause CNS-depression and narcosis. Prolonged inhalation can be harmful.

Skin : Prolonged skin contact may defat the skin and produce dermatitis. Prolonged or repeated exposure can cause skin irritation and redness.

Eyes : Can cause slight irritation, redness, tearing and blurred vision.

Ingestion : Intake can cause gastrointestinal irritation and nausea.

## WABO® NEOLUBE

Version 2.2

07/26/2006

Chronic exposure : This product contains solvents. Reports associate repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Reports also indicate that solvents cause liver damage, kidney damage, and mucous membrane irritation. Be warned that intentional misuse by deliberately inhaling the vapors and/or the product contents (a process often called "sniffing") can be harmful or fatal.

### Carcinogenicity

	ACGIH	IARC	NTP	OSHA
TOLUENE	Not classifiable as a human carcinogen.	Inadequate data.	N.E.	N.E.
XYLENE	Not classifiable as a human carcinogen.	Classification not possible from current data.	N.E.	N.E.
ETHYL BENZENE	Confirmed animal carcinogen with unknown relevance to humans.	Inadequate data.	N.E.	N.E.

## 4. FIRST AID MEASURES

Eye contact : Flush eyes with water, lifting upper and lower lids occasionally for 15 minutes. Seek medical attention.

Skin contact : Remove contaminated clothing. Wash thoroughly with soap and water. If irritation persists seek medical attention. Wash contaminated clothing before reuse.

Ingestion : Do not induce vomiting without medical advice. If conscious, drink plenty of water. If a person feels unwell or symptoms of skin irritation appear, consult a physician. If a person vomits, place him/her in the recovery position. Never give anything by mouth to an unconscious person.

Inhalation : Remove victim from exposure. If difficulty with breathing, administer oxygen. If breathing has stopped administer artificial respiration, preferably mouth-to-mouth. Seek immediate medical attention.

## 5. FIRE-FIGHTING MEASURES

Flash point : 39.9 °F (4.4 °C)

Autoignition temperature : no data available

Lower explosion limit : 1 %(V)

Upper explosion limit : 7 %(V)

Suitable extinguishing media : water fog  
dry chemical  
carbon dioxide (CO<sub>2</sub>)  
foam

Fire and Explosion Hazards : Flammable Liquid. Can release vapors that form explosive mixtures at temperatures at or above the flashpoint. Vapors can travel to a source of ignition and flash back. Empty containers retain product residue (liquid and/or vapor) and can be dangerous. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION; CONTAINERS MAY EXPLODE AND CAUSE INJURY OR DEATH. Heating can release vapours which can be ignited. Solid stream of water or

## WABO® NEOLUBE

Version 2.2

07/26/2006

foam can cause frothing.

Special Fire-fighting Procedures : Can be ignited by heat, sparks or flame. At higher temperature pressure build up in sealed containers. Use water to cool containers exposed to fire. As in any fire, wear pressure demand self-contained breathing apparatus (NIOSH approved or equivalent) and full protective gear. Water runoff can cause environmental damage. Dike and collect water used to fight fire.

---

## 6. ACCIDENTAL RELEASE MEASURES

---

Methods for cleaning up : Ventilate the area and remove all sources of ignition. Evacuate unnecessary personnel. Take action to eliminate source of leak. Large spills should be handled carefully. Put on respiratory protection and necessary personal protective equipment. Dike or impound spilled Liquid. Contain and collect spillage with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

---

## 7. HANDLING AND STORAGE

---

Handling : Keep out of reach of children. Use only in area provided with appropriate ventilation. Take precautionary measures against static discharges. Ground and bound containers when transferring material. For personal protection see section 8.

Storage : Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. Keep container tightly closed.

---

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

---

Eye protection : Wear as appropriate:  
safety glasses with side-shields  
goggles  
face-shield

Hand protection : Wear Chemically resistant gloves.

Body Protection : Wear as appropriate:  
Chemically resistant clothes  
preventive skin protection

Respiratory protection : In case of insufficient ventilation wear suitable respiratory equipment. When workers are facing concentrations above the exposure limit they must use NIOSH approved respirators.

Hygienic Practices : Avoid contact with skin, eyes and clothing. Ensure adequate ventilation, especially in confined areas. Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke. Handle in accordance with good industrial hygiene and safety practice.

Engineering Controls : Local exhaust ventilation can be necessary to control any air contaminants to within their TLVs during the use of this product.

---

## 9. PHYSICAL AND CHEMICAL PROPERTIES

---

Color : amber

## WABO® NEOLUBE

Version 2.2

07/26/2006

Physical State	: liquid
Odor	: aromatic
pH	: no data available
Odor Threshold	: no data available
Vapor Pressure	: 22 mm/Hg at 68 °F (20 °C)
Vapor Density	: 3.2 (Air = 1)
Boiling point/range	: 231.1 °F (110.6 °C)
Freeze Point	: no data available
Water solubility	: negligible
Specific Gravity	: 0.96
Viscosity	: no data available
Evaporation rate	: 0.6
Partition coefficient (n-octanol/water)	: no data available
VOC Concentration as applied (less water and exempt solvents)	: 716 g/l

---

## 10. STABILITY AND REACTIVITY

---

Stability	: Stable under recommended storage conditions.
Conditions to avoid	: Heat, flames and sparks. Direct sources of heat. Strong sunlight for prolonged periods. Prolonged exposure to high temperatures
Materials to avoid	: strong oxidizing agents
Hazardous decomposition products	: Oxides of carbon hydrogen chloride gas Oxides of sulfur
Hazardous polymerization	: Will not occur under normal conditions.

---

## 11. TOXICOLOGICAL INFORMATION

---

### Acute inhalation toxicity

<u>Type</u>	<u>Value</u>	<u>Species</u>	<u>Exposure time</u>
-------------	--------------	----------------	----------------------

## WABO® NEOLUBE

Version 2.2

07/26/2006

Product LC50 no data available

Component

TOLUENE LC50 no data available  
 XYLENE LC50 no data available  
 ETHYL BENZENE LC50 no data available

### Acute oral toxicity

<u>Product</u>	<u>Type</u>	<u>Value</u>	<u>Species</u>
	LD50 (Oral)	no data available	

Component

TOLUENE	LD50 (Oral)	636 mg/kg	
XYLENE	LD50 (Oral)	4,300 mg/kg	rat
ETHYL BENZENE	LD50 (Oral)	no data available	

### Acute dermal toxicity

<u>Product</u>	<u>Type</u>	<u>Value</u>	<u>Species</u>
	LD50 (Dermal)	no data available	

Component

TOLUENE	LD50 (Dermal)	20 mg/kg	
XYLENE	LD50 (Dermal)	> 1,700 mg/kg	rabbit
ETHYL BENZENE	LD50 (Dermal)	no data available	

## 12. ECOLOGICAL INFORMATION

Ecotoxicological Information : There is no data available for this product.

## 13. DISPOSAL CONSIDERATIONS

Recommendations: Use excess product in an alternate beneficial application. Handle disposal of waste material in manner which complies with local, state, province and federal regulation.

## 14. TRANSPORT INFORMATION

DOT	: Proper shipping name	ADHESIVES
	UN-No	<b>1133</b>
	Class	3
	Packaging group	III
	Primary Label	Flammable liquid

IATA	: Proper shipping name	ADHESIVES
	UN-No	<b>1133</b>
	Class	3

**WABO® NEOLUBE**

Version 2.2

07/26/2006

Packaging group III  
Primary Label Flammable liquid

**15. REGULATORY INFORMATION****SARA 311/312 (RTK)**

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendments and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

IMMEDIATE (ACUTE) HEALTH HAZARD DELAYED (CHRONIC) HEALTH HAZARD FIRE HAZARD

**SARA 313**

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

<u>Weight %</u>	<u>CAS No.</u>	<u>Chemical Name</u>
40.00 - 70.00 %	108-88-3	TOLUENE
5.00 - 10.00 %	1330-20-7	XYLENE
1.00 - 5.00 %	100-41-4	ETHYL BENZENE

**CERCLA**

CERCLA section 103(a) specifically requires the person in charge of a vessel or facility to report immediately to the National Response Center (NRC) a release of a hazardous substance whose amount equals or exceeds the assigned RQ. The following hazardous substances are contained in this product.

<u>RQ</u>	<u>CAS No.</u>	<u>Chemical Name</u>
1,000 lbs	108-88-3	TOLUENE
100 lbs	1330-20-7	XYLENE
1,000 lbs	100-41-4	ETHYL BENZENE

**TSCA Section 12(b) Export Notification**

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(b) if exported from the United States:

<u>CAS No.</u>	<u>Chemical Name</u>
----------------	----------------------

There are no TSCA 12(b) Chemicals in this product.

**California Proposition 65**

The chemical(s) noted below and contained in this product, are known to the state of California to cause cancer, birth defects or other reproductive harm. Unless otherwise specified in Section 2 of this MSDS, these chemicals are present at < 0.1%:

<u>CAS No.</u>	<u>Chemical Name</u>
108-88-3	TOLUENE
100-41-4	ETHYL BENZENE

**16. OTHER INFORMATION**

Legend : N.E. - Not Established  
TLV - Threshold Limit Value  
STEL - Short Term Exposure Limit  
PEL - Permissible Exposure Limit  
CEIL - Ceiling

## WABO® NEOLUBE

Version 2.2

07/26/2006

Prepared By : Environment, Health and Safety Department

This information is furnished without warranty, representation, or license of any kind, except that this information is accurate to the best of the manufacturer's knowledge, or is obtained from sources believed by the manufacturer to be accurate and is not intended to be all inclusive. No warranty is expressed or implied regarding the accuracy of this information or the results to be obtained from its use thereof. The manufacturer assumes no responsibility for injuries proximately caused by use of the Material if reasonable safety procedures are not followed as stipulated in this Data Sheet. Additionally, the manufacturer assumes no responsibility for injuries proximately caused by abnormal use of the Material even if reasonable safety procedures are followed. Buyer assumes the risk in its use of the Material.

End of MSDS.