

WABO® SILICONE SEALANT, PART A

Version 1.2

06/30/2006

1. PRODUCT AND COMPANY INFORMATION

Company : **Watson Bowman Acme Corporation**
95 Pineview Drive
Amherst, NY 14228

Telephone : 716-691-7566

Emergency telephone number : (800) 424-9300
(703) 527-3887 (Outside Continental US)

Product name : WABO® SILICONE SEALANT, PART A

MSDS ID No. : 10520

TSCA Inventory : All components of this product are included, or are exempt from inclusion, in the EPA Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

Canadian DSL : This product contains material not included on the Canadian Domestic Substance List (DSL).

Product Use Description : Sealant

2. HAZARDOUS INGREDIENTS

<u>Chemical</u>	<u>CAS No.</u>	<u>TLV</u>	<u>STEL</u>	<u>PEL</u>	<u>CEIL</u>	<u>Weight %</u>
POLY(DIMETHYLSILOXANE), HYDROXY TERMINATED	70131-67-8		N.E.	N.E.	N.E.	30.00 - 60.00 %
POLY(DIMETHYLSILOXANE) OXIMINO SILANES	63148-62-9	N.E.	N.E.	N.E.	N.E.	10.00 - 30.00 %
TOLUENE	Proprietary	N.E.	N.E.	N.E.	N.E.	5.00 - 10.00 %
	108-88-3	50 ppm	150 ppm	N.E.	300 ppm	1.00 - 5.00 %

3. HAZARDS IDENTIFICATION

HMIS® Rating : HEALTH 2 FLAMMABILITY 1 PHYSICAL HAZARD 1

WHMIS Class : D2B

Primary Routes of Entry : Ingestion
Inhalation
Eye contact
Skin contact
Skin absorption

Effects of Overexposure

Inhalation : Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. Inhalation of high vapor concentrations can cause CNS-depression and narcosis. Prolonged inhalation can be harmful.

Skin : Prolonged skin contact may defat the skin and produce dermatitis. Prolonged or repeated exposure can cause skin irritation and redness. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. May cause sensitization

WABO® SILICONE SEALANT, PART A

Version 1.2

06/30/2006

by skin contact. Components of the product may be absorbed into the body through the skin. When this product is exposed to moisture, Methyl Ethyl Ketoxime may be formed. Methyl Ethyl Ketoxime may be absorbed through the skin reducing the blood's ability to transport oxygen (methemoglobinemia and anemia).

- Eyes** : Can cause moderate to severe irritation, tearing and blurred vision. Prolonged exposure can result in more severe irritation and possible corneal injury.
- Ingestion** : Intake can cause gastrointestinal irritation, nausea, vomiting, diarrhea, headache, and drowsiness. Can cause moderate to severe irritation.
- Chronic exposure** : Existing respiratory or skin ailments may be aggravated by exposure. This product contains solvents. Reports associate repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Reports also indicate that solvents cause liver damage, kidney damage, and mucous membrane irritation. Be warned that intentional misuse by deliberately inhaling the vapors and/or the product contents (a process often called "sniffing") can be harmful or fatal.

Carcinogenicity

	ACGIH	IARC	NTP	OSHA
POLY(DIMETHYLSILOXANE), HYDROXY TERMINATED	N.E.	N.E.	N.E.	N.E.
POLY(DIMETHYLSILOXANE)	N.E.	N.E.	N.E.	N.E.
OXIMINO SILANES	N.E.	N.E.	N.E.	N.E.
TOLUENE	Not classifiable as a human carcinogen.	Inadequate data.	N.E.	N.E.

4. FIRST AID MEASURES

- Eye contact** : Flush eyes with water, lifting upper and lower lids occasionally for 15 minutes. Seek medical attention.
- Skin contact** : Remove contaminated clothing. Wash thoroughly with soap and water. If irritation persists seek medical attention. Wash contaminated clothing before reuse.
- Ingestion** : Do not induce vomiting without medical advice. If conscious, drink plenty of water. If a person feels unwell or symptoms of skin irritation appear, consult a physician. If a person vomits, place him/her in the recovery position. Never give anything by mouth to an unconscious person.
- Inhalation** : Remove victim from exposure. If difficulty with breathing, administer oxygen. If breathing has stopped administer artificial respiration, preferably mouth-to-mouth. Seek immediate medical attention.

5. FIRE-FIGHTING MEASURES

- Flash point** : > 200.01 °F (93.34 °C)
- Autoignition temperature** : no data available
- Lower explosion limit** : no data available
- Upper explosion limit** : no data available
- Suitable extinguishing media** : dry chemical
carbon dioxide (CO₂)
water fog
foam

WABO® SILICONE SEALANT, PART A

Version 1.2

06/30/2006

- Fire and Explosion Hazards : Containers can build up pressure if exposed to heat (fire). Cool closed containers exposed to fire with water spray. Solid stream of water or foam can cause frothing. Fire may produce irritating or poisonous fumes.
- Special Fire-fighting Procedures : As in any fire, wear pressure demand self-contained breathing apparatus (NIOSH approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

- Methods for cleaning up : Wear appropriate protective equipment (refer to section 8). Take action to eliminate source of leak; prevent from entry into open streams or sewers; contain spill by diking; vacuum up liquid or use absorbent media; remove to storage for disposal and rinse residual stain with water.

7. HANDLING AND STORAGE

- Handling : Use only in area provided with appropriate ventilation. Keep out of reach of children. For personal protection see section 8.
- Storage : Keep tightly closed in a dry and cool place.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

- Eye protection : Wear as appropriate:
safety glasses with side-shields
goggles
face-shield
- Hand protection : Wear as appropriate:
impervious gloves
- Body Protection : Wear as appropriate:
impervious clothing
preventive skin protection
- Respiratory protection : In case of insufficient ventilation wear suitable respiratory equipment. When workers are facing concentrations above the exposure limit they must use NIOSH approved respirators.
- Hygienic Practices : Avoid contact with skin, eyes and clothing. Ensure adequate ventilation, especially in confined areas. Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke. Handle in accordance with good industrial hygiene and safety practice.
- Engineering Controls : Local exhaust ventilation can be necessary to control any air contaminants to within their TLVs during the use of this product.

9. PHYSICAL AND CHEMICAL PROPERTIES

- Color : white
- Physical State : liquid

WABO® SILICONE SEALANT, PART A

Version 1.2

06/30/2006

Odor	:	slight aromatic
pH	:	not applicable
Odor Threshold	:	no data available
Vapor Pressure	:	no data available
Vapor Density	:	no data available
Boiling point/range	:	>230 °F (110 °C)
Freeze Point	:	no data available
Water solubility	:	insoluble
Specific Gravity	:	1.08
Viscosity	:	no data available
Evaporation rate	:	no data available
Partition coefficient (n-octanol/water)	:	no data available
VOC Concentration as applied (less water and exempt solvents)	:	< 41 g/l Note: VOC concentration expressed as applied when all components are mixed and applied per manufacturer's instructions.

10. STABILITY AND REACTIVITY

Stability	:	Stable under recommended storage conditions.
Conditions to avoid	:	Prolonged exposure to high temperatures
Materials to avoid	:	Water acids oxidizing agents metals
Hazardous decomposition products	:	Oxides of carbon nitrogen oxides (NOx) Reaction with water will release Methyl Ethyl Ketoxime.
Hazardous polymerization	:	May occur. Avoid exposure to water, strong acids, and heat treatment, especially in the presence of iron.

11. TOXICOLOGICAL INFORMATION

Acute inhalation toxicity

<u>Product</u>	<u>Type</u>	<u>Value</u>	<u>Species</u>	<u>Exposure time</u>
	LC50	no data available		
<u>Component</u>				

WABO® SILICONE SEALANT, PART A

Version 1.2

06/30/2006

POLY(DIMETHYLSILOXANE), HYDROXY TERMINATED	LC50	no data available
POLY(DIMETHYLSILOXANE)	LC50	no data available
OXIMINO SILANES	LC50	no data available
TOLUENE	LC50	no data available

Acute oral toxicity

<u>Product</u>	<u>Type</u>	<u>Value</u>	<u>Species</u>
	LD50 (Oral)	no data available	

Component

POLY(DIMETHYLSILOXANE), HYDROXY TERMINATED	LD50 (Oral)	no data available
POLY(DIMETHYLSILOXANE)	LD50 (Oral)	no data available
OXIMINO SILANES	LD50 (Oral)	no data available
TOLUENE	LD50 (Oral)	636 mg/kg

Acute dermal toxicity

<u>Product</u>	<u>Type</u>	<u>Value</u>	<u>Species</u>
	LD50 (Dermal)	no data available	

Component

POLY(DIMETHYLSILOXANE), HYDROXY TERMINATED	LD50 (Dermal)	no data available
POLY(DIMETHYLSILOXANE)	LD50 (Dermal)	no data available
OXIMINO SILANES	LD50 (Dermal)	no data available
TOLUENE	LD50 (Dermal)	20 mg/kg

12. ECOLOGICAL INFORMATION

Ecotoxicological Information : There is no data available for this product.

13. DISPOSAL CONSIDERATIONS

Recommendations: Use excess product in an alternate beneficial application. Handle disposal of waste material in manner which complies with local, state, province and federal regulation.

14. TRANSPORT INFORMATION

DOT	: Proper shipping name	Not regulated
IATA	: Proper shipping name	Not regulated

WABO® SILICONE SEALANT, PART A

Version 1.2

06/30/2006

15. REGULATORY INFORMATION**SARA 311/312 (RTK)**

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendments and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

IMMEDIATE (ACUTE) HEALTH HAZARD

SARA 313

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

<u>Weight %</u>	<u>CAS No.</u>	<u>Chemical Name</u>
1.00 - 5.00 %	108-88-3	TOLUENE

CERCLA

CERCLA section 103(a) specifically requires the person in charge of a vessel or facility to report immediately to the National Response Center (NRC) a release of a hazardous substance whose amount equals or exceeds the assigned RQ. The following hazardous substances are contained in this product.

<u>RQ</u>	<u>CAS No.</u>	<u>Chemical Name</u>
1,000 lbs	108-88-3	TOLUENE

TSCA Section 12(b) Export Notification

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(b) if exported from the United States:

<u>CAS No.</u>	<u>Chemical Name</u>
----------------	----------------------

There are no TSCA 12(b) Chemicals in this product.

California Proposition 65

The chemical(s) noted below and contained in this product, are known to the state of California to cause cancer, birth defects or other reproductive harm. Unless otherwise specified in Section 2 of this MSDS, these chemicals are present at < 0.1%:

<u>CAS No.</u>	<u>Chemical Name</u>
108-88-3	TOLUENE

16. OTHER INFORMATION

Legend : N.E. - Not Established
TLV - Threshold Limit Value
STEL - Short Term Exposure Limit
PEL - Permissible Exposure Limit
CEIL - Ceiling

Prepared By : Environment, Health and Safety Department

This information is furnished without warranty, representation, or license of any kind, except that this information is accurate to the best of the manufacturer's knowledge, or is obtained from sources believed by the manufacturer to be accurate and is not intended to be all inclusive. No warranty is expressed or implied regarding the accuracy of this information or the results to be obtained from its use thereof. The manufacturer assumes no responsibility for injuries proximately caused by use of the Material if reasonable safety procedures are not followed as stipulated in this Data Sheet. Additionally, the manufacturer assumes no responsibility for

WABO® SILICONE SEALANT, PART A

Version 1.2

06/30/2006

injuries proximately caused by abnormal use of the Material even if reasonable safety procedures are followed. Buyer assumes the risk in its use of the Material.

End of MSDS.