

WABO® PASTE ADHESIVE WARM WEATHER, PART B

Version 1.3

06/30/2006

1. PRODUCT AND COMPANY INFORMATION

Company : **Watson Bowman Acme Corporation**
95 Pineview Drive
Amherst, NY 14228

Telephone : 716-691-7566

Emergency telephone number : (800) 424-9300
(703) 527-3887 (Outside Continental US)

Product name : WABO® PASTE ADHESIVE WARM WEATHER, PART B

MSDS ID No. : 10526

TSCA Inventory : All components of this product are included, or are exempt from inclusion, in the EPA Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

Canadian DSL : All components of this product are included, or are exempt from inclusion, in the Canadian Domestic Substance List (DSL).

Product Use Description : Adhesive

2. HAZARDOUS INGREDIENTS

<u>Chemical</u>	<u>CAS No.</u>	<u>TLV</u>	<u>STEL</u>	<u>PEL</u>	<u>CEIL</u>	<u>Weight %</u>
SILICA, CRYSTALLINE QUARTZ	14808-60-7	0.05 mg/m3	N.E.	0.1 mg/m3	N.E.	30.00 - 60.00 %
POLYAMIDE RESIN	68082-29-1	N.E.	N.E.	N.E.	N.E.	15.00 - 40.00 %
2,4,6-TRIS((DIMETHYLAMINO)METHYL)PHENOL	90-72-2	N.E.	N.E.	N.E.	N.E.	2.00 - 7.00 %
TREATED FUMED SILICA	67762-90-7	N.E.	N.E.	N.E.	N.E.	1.00 - 5.00 %

3. HAZARDS IDENTIFICATION

HMIS® Rating : HEALTH 2* FLAMMABILITY 1 PHYSICAL HAZARD 0

WHMIS Class : D2B
E

Primary Routes of Entry : Inhalation
Skin contact
Eye contact

Effects of Overexposure

Inhalation : Harmful by inhalation. May cause sensitization by inhalation.

Skin : Can cause severe irritation and possible burns. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. May cause sensitization by skin contact.

Eyes : Corrosive. Can cause severe irritation, redness, tearing and blurred vision. Prolonged or

WABO® PASTE ADHESIVE WARM WEATHER, PART B

Version 1.3

06/30/2006

repeated contact can cause burns and possibly corneal injury.

Ingestion : Corrosive. Intake can cause burns of mouth, esophagus and stomach. Gastrointestinal burns, nausea, vomiting and diarrhea.

Chronic exposure : Existing respiratory or skin ailments may be aggravated by exposure. This product contains Crystalline (quartz) Silica which has been listed as a human carcinogen by NTP (Group 1) and IARC (Human Carcinogen) and a Suspected Human Carcinogen by ACGIH (category A2). Repeated or prolonged over exposure to free respirable Crystalline (quartz) silica can cause silicosis or other delayed and serious lung injury. No exposure to respirable Crystalline (quartz) Silica anticipated with recommended use of product.

Carcinogenicity

	ACGIH	IARC	NTP	OSHA
SILICA, CRYSTALLINE QUARTZ	Suspected human carcinogen.	Human carcinogen.		N.E.
POLYAMIDE RESIN	N.E.	N.E.	N.E.	N.E.
2,4,6-TRIS((DIMETHYLAMINO)METHYL)PHE NOL	N.E.	N.E.	N.E.	N.E.
TREATED FUMED SILICA	N.E.	N.E.	N.E.	N.E.

4. FIRST AID MEASURES

Eye contact : Flush eyes with water, lifting upper and lower lids occasionally for 15 minutes. Seek medical attention.

Skin contact : Remove contaminated clothing. Wash thoroughly with soap and water. If irritation persists seek medical attention. Wash contaminated clothing before reuse.

Ingestion : Do not induce vomiting without medical advice. If conscious, drink plenty of water. If a person feels unwell or symptoms of skin irritation appear, consult a physician. If a person vomits, place him/her in the recovery position. Never give anything by mouth to an unconscious person.

Inhalation : Remove victim from exposure. If difficulty with breathing, administer oxygen. If breathing has stopped administer artificial respiration, preferably mouth-to-mouth. Seek immediate medical attention.

5. FIRE-FIGHTING MEASURES

Flash point : > 199.9 °F (93.3 °C)

Autoignition temperature : no data available

Lower explosion limit : no data available

Upper explosion limit : no data available

Suitable extinguishing media : water spray
foam
carbon dioxide (CO2)
dry chemical
water fog

Fire and Explosion Hazards : Containers can build up pressure if exposed to heat (fire). Cool closed containers exposed to fire with water spray.

WABO® PASTE ADHESIVE WARM WEATHER, PART B

Version 1.3

06/30/2006

Special Fire-fighting Procedures : As in any fire, wear pressure demand self-contained breathing apparatus (NIOSH approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Methods for cleaning up : Evacuate personnel to safe areas. Wear personal protective equipment (refer to section 8). Contain spill immediately. Soak up with inert absorbent material. Take up mechanically and collect in suitable container for disposal.

7. HANDLING AND STORAGE

Handling : Keep out of reach of children. For personal protection see section 8.

Storage : Store in a place accessible by authorized persons only. Keep tightly closed.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Eye protection : Wear as appropriate:
safety glasses with side-shields
goggles
face-shield

Hand protection : Wear Chemically resistant gloves.

Body Protection : Wear as appropriate:
Chemically resistant clothes
preventive skin protection

Respiratory protection : In case of insufficient ventilation wear suitable respiratory equipment. When workers are facing concentrations above the exposure limit they must use NIOSH approved respirators.

Hygienic Practices : Avoid contact with skin, eyes and clothing. Ensure adequate ventilation, especially in confined areas. Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke. Handle in accordance with good industrial hygiene and safety practice.

Engineering Controls : Local exhaust ventilation can be necessary to control any air contaminants to within their TLVs during the use of this product.

9. PHYSICAL AND CHEMICAL PROPERTIES

Color : dark amber

Physical State : paste

Odor : characteristic

pH : not applicable

Odor Threshold : no data available

Vapor Pressure : no data available

WABO® PASTE ADHESIVE WARM WEATHER, PART B

Version 1.3

06/30/2006

Vapor Density	:	Heavier than air
Boiling point/range	:	no data available
Freeze Point	:	no data available
Water solubility	:	negligible
Specific Gravity	:	1.57
Viscosity	:	no data available
Evaporation rate	:	no data available
Partition coefficient (n-octanol/water)	:	no data available
VOC Concentration as applied (less water and exempt solvents)	:	0 g/l

10. STABILITY AND REACTIVITY

Stability	:	Stable under recommended storage conditions.
Conditions to avoid	:	Prolonged exposure to high temperatures
Materials to avoid	:	Strong oxidizing agents, acids, isocyanates and organic peroxides can result in violent explosive reaction. natural rubber
Hazardous decomposition products	:	Oxides of carbon nitrogen oxides (NOx) aldehydes ammonia
Hazardous polymerization	:	Will not occur under normal conditions.

11. TOXICOLOGICAL INFORMATION

Acute inhalation toxicity

<u>Product</u>	<u>Type</u>	<u>Value</u>	<u>Species</u>	<u>Exposure time</u>
	LC50	no data available		
<u>Component</u>				
SILICA, CRYSTALLINE QUARTZ	LC50	no data available		
POLYAMIDE RESIN	LC50	no data available		
2,4,6-TRIS((DIMETHYLAMINO)METHYL)PHENOL	LC50	no data available		
TREATED FUMED SILICA	LC50	no data available		

WABO® PASTE ADHESIVE WARM WEATHER, PART B

Version 1.3

06/30/2006

Acute oral toxicity

	Type	Value	Species
<u>Product</u>	LD50 (Oral)	no data available	
<u>Component</u>			
SILICA, CRYSTALLINE QUARTZ	LD50 (Oral)	1,300 mg/kg	
POLYAMIDE RESIN	LD50 (Oral)	5,000 mg/kg	
2,4,6-TRIS((DIMETHYLAMINO)METHYL)PHENOL	LD50 (Oral)	no data available	
TREATED FUMED SILICA	LD50 (Oral)	3,864 mg/kg	

Acute dermal toxicity

	Type	Value	Species
<u>Product</u>	LD50 (Dermal)	no data available	
<u>Component</u>			
SILICA, CRYSTALLINE QUARTZ	LD50 (Dermal)	no data available	
POLYAMIDE RESIN	LD50 (Dermal)	no data available	
2,4,6-TRIS((DIMETHYLAMINO)METHYL)PHENOL	LD50 (Dermal)	1,280 mg/kg	rabbit
TREATED FUMED SILICA	LD50 (Dermal)	no data available	

12. ECOLOGICAL INFORMATION

Ecotoxicological Information : There is no data available for this product.

13. DISPOSAL CONSIDERATIONS

Recommendations: Use excess product in an alternate beneficial application. Handle disposal of waste material in manner which complies with local, state, province and federal regulation.

14. TRANSPORT INFORMATION

DOT	: Proper shipping name	CORROSIVE LIQUID, N.O.S. (2,4,6-TRIS((DIMETHYLAMINO)METHYL)PHENOL)
	UN-No	1760
	Class	8
	Packaging group	III
	Primary Label	Corrosive
IATA	: Proper shipping name	CORROSIVE LIQUID, N.O.S. (2,4,6-TRIS((DIMETHYLAMINO)METHYL)PHENOL)
	UN-No	1760
	Class	8
	Packaging group	III
	Primary Label	Corrosive

15. REGULATORY INFORMATION

WABO® PASTE ADHESIVE WARM WEATHER, PART B

Version 1.3

06/30/2006

SARA 311/312 (RTK)

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendments and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

IMMEDIATE (ACUTE) HEALTH HAZARD DELAYED (CHRONIC) HEALTH HAZARD

SARA 313

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

<u>Weight %</u>	<u>CAS No.</u>	<u>Chemical Name</u>
-----------------	----------------	----------------------

This product contains no chemicals subject to the SARA 313 supplier notification requirements.

CERCLA

CERCLA section 103(a) specifically requires the person in charge of a vessel or facility to report immediately to the National Response Center (NRC) a release of a hazardous substance whose amount equals or exceeds the assigned RQ. The following hazardous substances are contained in this product.

<u>RQ</u>	<u>CAS No.</u>	<u>Chemical Name</u>
-----------	----------------	----------------------

No CERCLA chemicals exist in this product above reportable concentrations.

TSCA Section 12(b) Export Notification

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(b) if exported from the United States:

<u>CAS No.</u>	<u>Chemical Name</u>
----------------	----------------------

There are no TSCA 12(b) Chemicals in this product.

California Proposition 65

The chemical(s) noted below and contained in this product, are known to the state of California to cause cancer, birth defects or other reproductive harm. Unless otherwise specified in Section 2 of this MSDS, these chemicals are present at < 0.1%:

<u>CAS No.</u>	<u>Chemical Name</u>
14808-60-7	SILICA, CRYSTALLINE QUARTZ

16. OTHER INFORMATION

Legend	:	N.E. - Not Established TLV - Threshold Limit Value STEL - Short Term Exposure Limit PEL - Permissible Exposure Limit CEIL - Ceiling
Prepared By	:	Environment, Health and Safety Department

This information is furnished without warranty, representation, or license of any kind, except that this information is accurate to the best of the manufacturer's knowledge, or is obtained from sources believed by the manufacturer to be accurate and is not intended to be all inclusive. No warranty is expressed or implied regarding the accuracy of this information or the results to be obtained from its use thereof. The manufacturer assumes no responsibility for injuries proximately caused by use of the Material if reasonable

WABO® PASTE ADHESIVE WARM WEATHER, PART B

Version 1.3

06/30/2006

safety procedures are not followed as stipulated in this Data Sheet. Additionally, the manufacturer assumes no responsibility for injuries proximately caused by abnormal use of the Material even if reasonable safety procedures are followed. Buyer assumes the risk in its use of the Material.

End of MSDS.