

Safety Data Sheet

WABO PASTE ADHESIVE WARM WEATHER PART A

Revision date : 2010/04/21

Page: 1/6

Version: 1.0

(298891/SDS_GEN_CA/EN)

1. Product and Company Identification

Company

Watson Bowman Acme Corporation
95 Pineview Drive
Amherst, NY 14228 USA

24 Hour Emergency Response Information

CANUTEC (reverse charges): (613) 996-6666
BASF HOTLINE: (800) 454-COPE (2673)

2. Hazards Identification

Emergency overview

IRRITANT.
SENSITIZER.
Irritating to eyes and skin.
May cause sensitization by skin contact.
CONTAINS MATERIAL WHICH CAN CAUSE CANCER.

State of matter: solid
Colour: light grey
Odour: sweetish

Potential health effects**Irritation / corrosion:**

Prolonged contact with the product can result in skin irritation. May cause slight irritation to the eyes.

Sensitization:

May cause allergic skin reaction.

Potential environmental effects**Aquatic toxicity:**

No data available concerning aquatic toxicity.

3. Composition / Information on Ingredients

<u>CAS Number</u>	<u>Content (W/W)</u>	<u>Hazardous ingredients</u>
14808-60-7	>= 40.0 - <= 70.0 %	crystalline silica
25068-38-6	>= 15.0 - <= 40.0 %	bisphenol A-epichlorohydrin resin
2210-79-9	>= 7.0 - <= 13.0 %	Oxirane, 2-[(2-methylphenoxy)methyl]-

Safety Data Sheet

WABO PASTE ADHESIVE WARM WEATHER PART A

Revision date : 2010/04/21

Version: 1.0

Page: 2/6

(298891/SDS_GEN_CA/EN)

4. First-Aid Measures

General advice:

First aid personnel should pay attention to their own safety. Remove contaminated clothing.

If on skin:

After contact with skin, wash immediately with plenty of water and soap. Under no circumstances should organic solvent be used. If irritation develops, seek medical attention.

If in eyes:

Wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

If swallowed:

Rinse mouth immediately with water. Seek medical attention if necessary. Do not induce vomiting unless told to by a poison control center or doctor.

5. Fire-Fighting Measures

Flash point: 94 °C

Suitable extinguishing media:

carbon dioxide, dry extinguishing media, foam, water fog, water spray

Hazards during fire-fighting:

carbon dioxide, carbon monoxide, harmful vapours, nitrogen oxides, fumes/smoke, carbon black

Protective equipment for fire-fighting:

Wear a self-contained breathing apparatus.

Further information:

The degree of risk is governed by the burning substance and the fire conditions. Contaminated extinguishing water must be disposed of in accordance with official regulations.

6. Accidental release measures

Personal precautions:

Use personal protective clothing. Avoid contact with the skin, eyes and clothing. Handle in accordance with good building materials hygiene and safety practice.

Environmental precautions:

Contain contaminated water/firefighting water. Do not discharge into drains/surface waters/groundwater.

Cleanup:

For small amounts: Sweep/shovel up. Dispose of absorbed material in accordance with regulations.

For large amounts: Sweep/shovel up. Dispose of absorbed material in accordance with regulations.

7. Handling and Storage

Handling

General advice:

Avoid contact with the skin, eyes and clothing.

Safety Data Sheet

WABO PASTE ADHESIVE WARM WEATHER PART A

Revision date : 2010/04/21

Page: 3/6

Version: 1.0

(298891/SDS_GEN_CA/EN)

Protection against fire and explosion:

The substance/product is non-combustible. The product does not contribute to the spreading of flames, nor is it self combustible, not explosive.

Storage

General advice:

Keep only in the original container in a cool, well-ventilated place. Protect from direct sunlight. Store protected against freezing.

8. Exposure Controls and Personal Protection

Components with workplace control parameters

crystalline silica	OSHA	TWA value 2.4 millions of particles per cubic foot of air Respirable ; The value is calculated from a specified equation using a value of 100%. Lower values of % will give higher exposure limits. See regulation for specific equation. TWA value 0.1 mg/m3 Respirable ; The value is calculated from a specified equation using a value of 100%. Lower values of % will give higher exposure limits. See regulation for specific equation. TWA value 0.3 mg/m3 Total dust ; The value is calculated from a specified equation using a value of 100%. Lower values of % will give higher exposure limits. See regulation for specific equation.
	ACGIH	TWA value 0.025 mg/m3 Respirable fraction ;

Personal protective equipment

Hand protection:

Wear chemical resistant protective gloves.

Eye protection:

Safety glasses with side-shields.

Body protection:

Body protection must be chosen based on level of activity and exposure.

General safety and hygiene measures:

Avoid contact with the skin, eyes and clothing. In order to prevent contamination while handling, closed working clothes and working gloves should be used. Handle in accordance with good building materials hygiene and safety practice. When using, do not eat, drink or smoke. Hands and/or face should be washed before breaks and at the end of the shift. At the end of the shift the skin should be cleaned and skin-care agents applied. Gloves must be inspected regularly and prior to each use. Replace if necessary (e.g. pinhole leaks).

9. Physical and Chemical Properties

Form:	paste	
Odour:	sweetish	
Odour threshold:	No data available.	
Colour:	light grey	
pH value:		not applicable
Melting point:		not applicable
Density:	1.76 g/cm3	
Partitioning coefficient n-octanol/water (log Pow):		not applicable

Safety Data Sheet

WABO PASTE ADHESIVE WARM WEATHER PART A

Revision date : 2010/04/21
Version: 1.0

Page: 4/6
(298891/SDS_GEN_CA/EN)

10. Stability and Reactivity

Conditions to avoid:

See MSDS section 7 - Handling and storage.

Substances to avoid:

strong acids, strong bases, strong oxidizing agents

Hazardous reactions:

The product is stable if stored and handled as prescribed/indicated.

Thermal decomposition:

No decomposition if stored and handled as prescribed/indicated.

Oxidizing properties:

Not an oxidizer.

11. Toxicological information

Irritation / corrosion

Information on: bisphenol A-epichlorohydrin resin

Assessment of irritating effects:

Eye contact causes irritation. Skin contact causes irritation.

Information on: Oxirane, 2-[(2-methylphenoxy)methyl]-

Assessment of irritating effects:

Eye contact causes irritation. Skin contact causes irritation.

Sensitization

Information on: bisphenol A-epichlorohydrin resin

Assessment of sensitization:

Sensitization after skin contact possible.

Information on: Oxirane, 2-[(2-methylphenoxy)methyl]-

Assessment of sensitization:

Caused skin sensitization in animal studies.

Carcinogenicity

Information on: crystalline silica

The International Agency for Research on Cancer (IARC) has classified this substance as a Group 1 (known) human carcinogen.

Experiences in humans:

According to experience, the product is considered to be harmless to health if used in the correct manner.

Other Information:

The product has not been tested. The statement has been derived from the properties of the individual components.

12. Ecological Information

Safety Data Sheet

WABO PASTE ADHESIVE WARM WEATHER PART A

Revision date : 2010/04/21
Version: 1.0

Page: 5/6
(298891/SDS_GEN_CA/EN)

Other adverse effects:

Do not allow to enter soil, waterways or waste water channels. According to experience, the material has no harmful effect on the environment.

13. Disposal considerations

Waste disposal of substance:

Dispose of in accordance with local authority regulations. Do not discharge into drains/surface waters/groundwater.

14. Transport Information

Land transport

TDG

Not classified as a dangerous good under transport regulations

Sea transport

IMDG

Not classified as a dangerous good under transport regulations

Air transport

IATA/ICAO

Not classified as a dangerous good under transport regulations

15. Regulatory Information

Federal Regulations

Registration status:

Chemical DSL, CA released / listed

WHMIS classification: D2B: Materials Causing Other Toxic Effects - Toxic material



THIS PRODUCT HAS BEEN CLASSIFIED IN ACCORDANCE WITH THE HAZARD CRITERIA OF THE CPR AND THE MSDS CONTAINS ALL THE INFORMATION REQUIRED BY THE CPR.

16. Other Information

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our

Safety Data Sheet

WABO PASTE ADHESIVE WARM WEATHER PART A

Revision date : 2010/04/21

Page: 6/6

Version: 1.0

(298891/SDS_GEN_CA/EN)

products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

MSDS Prepared by:

BASF NA Product Regulations

safety_ecology_canada@basf.com

MSDS Prepared on: 2010/04/21

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE , IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY BASF HEREUNDER ARE GIVEN GRATIS AND BASF ASSUMES NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

END OF DATA SHEET