

## ARMORED CONDITION


### SLAB-TO-SLAB CONDITION

Nominal Relaxed Dimensions	Movement Range					
	"A"	"B"	J.O. Min.	J.O. Max.	Total Movement	
Model	"A"	"B"	J.O. Min.	"C"	J.O. Max.	Total Movement
25FW	1"(25)	1 1/4"(32)	1 1/16"(17)	1/8"(3)	1 5/16"(34)	5/8"(16)
40FW	1-5/8"(41)	2"(51)	1"(25)	1/8"(3)	2"(51)	1"(25)
50FW	2"(51)	2-1/2"(64)	1-3/8"(35)	1/8"(3)	2-5/8"(66)	1-1/4"(32)
65FW	2-1/2"(64)	3 1/4"(82)	1-5/8"(41)	1/8"(3)	3-3/8"(86)	1-3/4"(44)
75FW	3"(76)	3 3/4"(95)	2"(51)	1/8"(3)	4"(102)	2"(51)
100FW	3 7/8"(100)	5"(127)	2-1/1/16"(68)	1/8"(3)	5-5/16"(135)	2-5/8"(67)
125FW	5"(127)	6 1/8"(155)	3-3/8"(86)	1/8"(3)	6-5/8"(168)	3-1/4"(83)

( ) - Denotes Millimeters

# Wabco®Jeene

Model: FW



Watson Bowman Acme Corp.

95 Pineview Drive Amherst, NY 14228

phone: (716) 691-7566

fax: (716) 691-9239

www.wbacorp.com



The Chemical Company

DATE: 12/14/06

CURRENT ISSUE: 12/14/06

DRAWING NO: C - 96011

SHEET NO: 11

Information provided herein, including but not limited to, any drawing, design, photograph, graphic, or statement is the property of Watson Bowman Acme Corporation ("Company"). Reproduction, translation, or reduction to any electronic medium or machine readable form, in whole or part, is strictly prohibited, except for the express purpose for which it has been furnished, without prior written consent of Company. All Materials contained herein are provided by Company for informational purposes only. Company reserves the right to amend or withdraw any information contained in the Material without notice. Mechanical drawings and specifications are subject to change without notice. The use of the information contained in this specific section ("Section") is given by Company and is void if this does not apply.