

WABO ELASTOPATCH TAN PART B

Version 1.2

06/28/2007

1. PRODUCT AND COMPANY INFORMATION

Company : **BASF Construction Chemicals, LLC**
 Watson Bowman Acme Corporation
 95 Pineview Drive
 Amherst, NY 14228

Telephone : 716-691-7566

Emergency telephone number : BASF ER HOTLINE: 800-832-4357
 CHEMTREC: 800-424-9300
 CHEMTREC (Outside Continental US): 703-527-3887

Product name : WABO ELASTOPATCH TAN PART B

MSDS ID No. : 12620

TSCA Inventory : All components of this product are included, or are exempt from inclusion, in the EPA Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

Canadian DSL : All components of this product are included, or are exempt from inclusion, in the Canadian Domestic Substance List (DSL).

Product Use Description : Concrete

2. HAZARDOUS INGREDIENTS

<u>Chemical</u>	<u>CAS No.</u>	<u>TLV</u>	<u>STEL</u>	<u>PEL</u>	<u>CEIL</u>	<u>Weight %</u>
CASTOR OIL	8001-79-4		N.E.	N.E.	N.E.	60.00 - 100.00 %
TITANIUM DIOXIDE	13463-67-7	10 mg/m3	N.E.	15 mg/m3	N.E.	1.00 - 5.00 %

3. HAZARDS IDENTIFICATION

HMIS® Rating : HEALTH 1 FLAMMABILITY 1 PHYSICAL HAZARD 0

WHMIS Class : D2B

Effects of Overexposure

Inhalation : Can cause slight irritation.

Skin : Can cause slight irritation.

Eyes : Can cause slight irritation.

Ingestion : Can cause slight irritation.

Chronic exposure : No known information available.

Carcinogenicity

	ACGIH	IARC	NTP	OSHA
CASTOR OIL	N.E.	N.E.	N.E.	N.E.
TITANIUM DIOXIDE	Not classifiable as a	Regard as if	N.E.	N.E.

WABO ELASTOPATCH TAN PART B

Version 1.2

06/28/2007

	human carcinogen.	carcinogenic for man.		
--	-------------------	-----------------------	--	--

4. FIRST AID MEASURES

- Eye contact : Flush eyes with water, lifting upper and lower lids occasionally for 15 minutes. Seek medical attention.
- Skin contact : Remove contaminated clothing. Wash thoroughly with soap and water. If irritation persists seek medical attention. Wash contaminated clothing before reuse.
- Ingestion : Do not induce vomiting without medical advice. If conscious, drink plenty of water. If a person feels unwell or symptoms of skin irritation appear, consult a physician. If a person vomits, place him/her in the recovery position. Never give anything by mouth to an unconscious person.
- Inhalation : Remove victim from exposure. If difficulty with breathing, administer oxygen. If breathing has stopped administer artificial respiration, preferably mouth-to-mouth. Seek immediate medical attention.

5. FIRE-FIGHTING MEASURES

- Flash point : Not combustible.
- Autoignition temperature : not applicable
- Lower explosion limit : not applicable
- Upper explosion limit : not applicable
- Suitable extinguishing media : carbon dioxide (CO₂)
dry chemical
foam
water fog
- Fire and Explosion Hazards : Containers can build up pressure if exposed to heat (fire). Cool closed containers exposed to fire with water spray.
- Special Fire-fighting Procedures : As in any fire, wear pressure demand self-contained breathing apparatus (NIOSH approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

- Methods for cleaning up : Wear appropriate protective equipment (refer to section 8). Take action to eliminate source of leak; prevent from entry into open streams or sewers; contain spill by diking; vacuum up liquid or use absorbent media; remove to storage for disposal and rinse residual stain with water.

7. HANDLING AND STORAGE

- Handling : Keep out of reach of children. For personal protection see section 8.
- Storage : Keep tightly closed.

WABO ELASTOPATCH TAN PART B

Version 1.2

06/28/2007

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Eye protection	:	Wear as appropriate: safety glasses with side-shields goggles face-shield
Hand protection	:	Wear as appropriate: impervious gloves
Body Protection	:	Wear as appropriate: impervious clothing preventive skin protection
Respiratory protection	:	In case of insufficient ventilation wear suitable respiratory equipment. When workers are facing concentrations above the exposure limit they must use NIOSH approved respirators.
Hygienic Practices	:	Avoid contact with skin, eyes and clothing. Ensure adequate ventilation, especially in confined areas. Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke. Handle in accordance with good industrial hygiene and safety practice.
Engineering Controls	:	Local exhaust ventilation can be necessary to control any air contaminants to within their TLVs during the use of this product.

9. PHYSICAL AND CHEMICAL PROPERTIES

Color	:	tan
Physical State	:	liquid
Odor	:	slight
pH	:	not applicable
Odor Threshold	:	no data available
Vapor Pressure	:	no data available
Vapor Density	:	no data available
Boiling point/range	:	no data available
Freeze Point	:	no data available
Water solubility	:	insoluble
Specific Gravity	:	1.01
Evaporation rate	:	Slower than Butyl acetate
Partition coefficient (n-octanol/water)	:	no data available
VOC Concentration as applied (less water and exempt solvents)	:	0 g/l Note: VOC concentration expressed as applied when all components are mixed and applied per manufacturer's instructions.

WABO ELASTOPATCH TAN PART B

Version 1.2

06/28/2007

10. STABILITY AND REACTIVITY

- Stability : Stable under recommended storage conditions.
- Conditions to avoid : Prolonged exposure to high temperatures
- Materials to avoid : strong acids and oxidizing agents
- Hazardous decomposition products : Oxides of carbon.
Thermal decomposition can lead to release of irritating gases and vapours.
- Hazardous polymerization : Will not occur under normal conditions.

11. TOXICOLOGICAL INFORMATION

Acute inhalation toxicity

<u>Product</u>	<u>Type</u> LC50	<u>Value</u> no data available	<u>Species</u>	<u>Exposure time</u>
<u>Component</u>				
CASTOR OIL	LC50	no data available		
TITANIUM DIOXIDE	LC50	no data available		

Acute oral toxicity

<u>Product</u>	<u>Type</u> LD50 (Oral)	<u>Value</u> no data available	<u>Species</u>
<u>Component</u>			
CASTOR OIL	LD50 (Oral)	no data available	
TITANIUM DIOXIDE	LD50 (Oral)	no data available	

Acute dermal toxicity

<u>Product</u>	<u>Type</u> LD50 (Dermal)	<u>Value</u> no data available	<u>Species</u>
<u>Component</u>			
CASTOR OIL	LD50 (Dermal)	no data available	
TITANIUM DIOXIDE	LD50 (Dermal)	no data available	

12. ECOLOGICAL INFORMATION

WABO ELASTOPATCH TAN PART B

Version 1.2

06/28/2007

Ecotoxicological Information : There is no data available for this product.

13. DISPOSAL CONSIDERATIONS

Recommendations: Use excess product in an alternate beneficial application. Handle disposal of waste material in manner which complies with local, state, province and federal regulation.

14. TRANSPORT INFORMATION

DOT	: Proper shipping name	Not regulated
IATA	: Proper shipping name	Not regulated

15. REGULATORY INFORMATION

SARA 311/312 (RTK)

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendments and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

IMMEDIATE (ACUTE) HEALTH HAZARD

SARA 313

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

<u>Weight %</u>	<u>CAS No.</u>	<u>Chemical Name</u>
-----------------	----------------	----------------------

This product contains no chemicals subject to the SARA 313 supplier notification requirements.

CERCLA

CERCLA section 103(a) specifically requires the person in charge of a vessel or facility to report immediately to the National Response Center (NRC) a release of a hazardous substance whose amount equals or exceeds the assigned RQ. The following hazardous substances are contained in this product.

<u>RQ</u>	<u>CAS No.</u>	<u>Chemical Name</u>
-----------	----------------	----------------------

No CERCLA chemicals exist in this product above reportable concentrations.

TSCA Section 12(b) Export Notification

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(b) if exported from the United States:

<u>CAS No.</u>	<u>Chemical Name</u>
----------------	----------------------

There are no TSCA 12(b) Chemicals in this product.

California Proposition 65

The chemical(s) noted below and contained in this product, are known to the state of California to cause cancer, birth defects or other reproductive harm. Unless otherwise specified in Section 2 of this MSDS, these chemicals are present at < 0.1%:

WABO ELASTOPATCH TAN PART B

Version 1.2

06/28/2007

<u>CAS No.</u>	<u>Chemical Name</u>
7439-92-1	INORGANIC LEAD

16. OTHER INFORMATION

Legend	:	N.E. - Not Established TLV - Threshold Limit Value STEL - Short Term Exposure Limit PEL - Permissible Exposure Limit CEIL - Ceiling
Prepared By	:	Environment, Health and Safety Department

This information is furnished without warranty, representation, or license of any kind, except that this information is accurate to the best of the manufacturer's knowledge, or is obtained from sources believed by the manufacturer to be accurate and is not intended to be all inclusive. No warranty is expressed or implied regarding the accuracy of this information or the results to be obtained from its use thereof. The manufacturer assumes no responsibility for injuries proximately caused by use of the Material if reasonable safety procedures are not followed as stipulated in this Data Sheet. Additionally, the manufacturer assumes no responsibility for injuries proximately caused by abnormal use of the Material even if reasonable safety procedures are followed. Buyer assumes the risk in its use of the Material.

End of MSDS.